

**STATE OF CALIFORNIA
CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
LOS ANGELES REGION
320 West 4th Street, Suite 200, Los Angeles, California 90013**

**FACT SHEET
WASTE DISCHARGE REQUIREMENTS
FOR
VOPAK TERMINAL LOS ANGELES INC.
(Inland Terminal Hydrostatic Test Project)**

**NPDES NO. CAG674001
CI-9554**

FACILITY ADDRESS

2200 E. Pacific Coast Highway
Wilmington, CA 90744

FACILITY MAILING ADDRESS

401 Canal Street
Wilmington, CA 90744

PROJECT DESCRIPTION:

Vopak Terminal Los Angeles Inc. (Vopak) proposes to conduct hydrostatic test of their Tank No. 108 prior to placing it back into service at Vopak's Inland Terminal facility located at 2200 E. Pacific Coast Highway, Wilmington. The Inland Terminal facility is a fuel oil and jet fuel storage depot. Tank No. 108 will be thoroughly cleaned by using pressurized steam and filled with domestic potable water before the hydrostatic test is conducted. Vopak proposes to complete this one time discharge in approximately 15 days. The hydrostatic test water will be analyzed prior to discharge to the nearby Dominguez Channel.

VOLUME AND DESCRIPTION OF DISCHARGE:

Up to 0.9 million gallons per day (MGD) of hydrostatic test water will be discharged to the on site storm drain at Latitude 33°47'30", Longitude 118°14'00", which drains to the Dominguez Channel, a water of the United States. The site location is shown in Figure 1.

APPLICABLE EFFLUENT LIMITATIONS

Based on the information provided in the NPDES Application Supplemental Requirements, the following constituents listed in the Table below have been determined to show reasonable potential to exist in the discharge. The discharge flows into Dominguez Channel. Therefore, effluent limitations in Attachment B are not applicable to the discharge.

October 15, 2009

This Table lists the specific constituents and effluent limitations applicable to the discharge.

Constituents	Units	Discharge Limitations	
		Daily Maximum	Monthly Average
Total Suspended Solids	mg/L	150	50
Turbidity	NTU	150	50
BOD ₅ 20°C	mg/L	30	20
Oil and Grease	mg/L	15	10
Settable Solids	ml/L	0.3	0.1
Residual Chlorine	mg/L	0.1	---

FREQUENCY OF DISCHARGE:

This one time discharge will last about 15 days.

REUSE OF WATER:

It is not feasible to discharge the wastewater to the sanitary sewer system. It is not economically feasible to haul the wastewater for off-site disposal. There are no feasible reuse options for the discharge. Therefore, the hydrostatic test water will be discharged into the storm drain in compliance with the requirements of the attached order.

Vopak Terminal Los Angeles
2200 E. Pacific Coast Hwy.
Wilmington, CA 90744

FIGURE 1

